




G-310/G-320 Flat



G-310/G-320 Flat Back



G-310/G-320 Pole



G-310/G-320 Pole Back

## Models

G-310: One communication protocol. Powered by mains.

G-310 B: One communication protocol. Powered by mains or rechargeable battery.

G-320: Several communication protocols (up to 60). Powered by mains.

G-320 B: Several communication protocols (up to 60). Powered by mains or rechargeable battery.

## Format

Flat or Tower.

Tower is included in the scale box and can be easily set up by the user.

## Capacity / Accuracy

6 kg - 2 g # 15 kg - 5 g / 15 kg - 5 g # 30 kg - 10 g.

## Display

2 Displays (vendor+customer). Backlight LCD. Weight - Price - Amount.

## Features

PLUs: 100.

Presets: 9 x 2.

Tare and tare fixing functions.

## Communications

Connection to computer, EPoS or ECR, by means of incorporated RS-232 port. Communication protocols available for the main brands and models in the market.

- Models with one protocol (G-310/G-310 B). The change of protocol is made by telecharging the new one from the PC.

- Multiprotocol models (G-320/G-320 B). The protocol is selected among all the possible ones in the scale. You can also incorporate new protocols (up to a maximum of 60) by telecharging them from computer.

## Power

Mains or Mains + rechargeable battery, depending on model.

In case of mains failure, the scale would automatically begin operating with rechargeable battery.

The internal battery is recharged from the very scale.

The auto switch-off time of the scale is programmable.

Last of batteries: up to 120 hours, with fully charged battery and backlight off.

## CE Approval



## Dimensions

